



型号 Housing No.	轴承座断裂负荷 (kN)					有帽螺栓		最大允许负荷 (kN)		
	Q180°	Q150°	Q120°	Q90°	Q55°	尺寸 (mm)	扭矩 (Nm)	Q180°	Q150°	Q120°
SNU505	80	60	70	95	155	M10×40	50	25	30	50
SNU506-605	85	65	80	100	170	M10×45	50	25	30	50
SNU507-606	95	80	85	115	190	M10×50	50	25	30	50
SNU508-607	110	85	95	130	215	M10×55	50	25	30	50
SNU509	115	90	100	140	230	M10×55	50	25	30	50
SNU510-608	130	110	120	155	265	M12×60	50	25	30	50
SNU511-609	140	115	125	170	275	M12×60	80	40	45	80
SNU512-610	150	120	130	180	300	M12×60	80	40	45	80
SNU513-611	170	130	150	205	340	M12×65	80	40	45	80
SNU515-612	205	160	185	250	410	M12×65	80	40	45	80
SNU516-613	215	175	190	260	430	M16×70	150	85	100	170
SNU517	240	190	205	290	480	M16×80	150	85	100	170
SNU518-615	275	215	250	340	550	M16×85	150	85	100	170
SNU519-616	290	230	260	350	580	M16×90	150	85	100	170
SNU520-617	310	250	280	370	620	M20×100	200	130	150	260
SNU522-619	340	270	310	410	680	M20×100	200	130	150	260
SNU524-620	400	320	350	470	790	M20×110	200	130	150	260
SNU526	450	360	410	540	900	M20×120	200	130	150	260
SNU528	530	430	470	630	1050	M20×120	200	130	150	260
SNU530	600	480	540	730	1200	M20×130	200	130	150	260
SNU532	720	570	640	860	1450	M20×130	200	130	150	260